

アルミ定尺板1(A1050P)

A1050P H24

○ 生地 ■ B2アルマイト

| 板厚 mm | 寸 法 mm | | | | | |
|-------|-------------|---------|-----------------|-------------|---------|-----------------|
| | 1000 × 2000 | | | 1250 × 2500 | | |
| | 生地 | B2アルマイト | 1枚の質量 (kg/枚) | 生地 | B2アルマイト | 1枚の質量 (kg/枚) |
| 0.3 | ○ | | 1.63 | | | |
| 0.4 | ○ | | 2.17 | | | |
| 0.5 | ○ | | 2.72 | | | |
| 0.6 | ○ | | 3.25 | | | |
| 0.8 | ○ | ■ | 4.34 | ○ | | 6.78 |
| 1.0 | ○ | ■ | 5.42 | ○ | ■ | 8.48 |
| 1.2 | ○ | ■ | 6.50 | ○ | | 10.16 |
| 1.5 | | | | | | |
| 2.0 | | | | | | |
| 2.5 | ○ | | 13.56 | | | |
| 3.0 | | | | | | |
| 4.0 | ○ | | 21.70 | | | |
| 5.0 | ○ | | 27.10 | | | |
| 6.0 | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

表記の質量はテーブル計算です。実際の商品とは異なる場合があります。

アルミ板定尺板2(A1100P)

A1100P H14

○ 国内材 ▲ 輸入材 □ B2アルマイト

| 板厚 mm | 寸 法 mm | | | | | | | | | | | |
|----------|-------------|-----|---------|-----------------|-------------|-----|---------|-----------------|-------------|-----|---------|-----------------|
| | 1000 x 2000 | | | | 1000 x 3000 | | | | 1250 x 2500 | | | |
| | 国内材 | 輸入材 | B2アルマイト | 1枚の質量 (kg/枚) | 国内材 | 輸入材 | B2アルマイト | 1枚の質量 (kg/枚) | 国内材 | 輸入材 | B2アルマイト | 1枚の質量 (kg/枚) |
| 1.5 | ○ | ▲ | □ | 8.13 | ○ | | □ | 12.2 | ○ | ▲ | □ | 12.7 |
| 2.0 | ○ | ▲ | □ | 10.84 | ○ | ▲ | □ | 16.3 | ○ | ▲ | □ | 17.0 |
| 2.5 | | | | | | | | | ○ | | | 21.2 |
| 3.0 | ○ | ▲ | □ | 16.25 | | | | | ○ | ▲ | □ | 25.4 |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |

表記の質量はテーブル計算です。実際の商品とは異なる場合があります。

アルミ板定尺板3(A1100P)

A1100P H14

○ 国内材 ▲ 輸入材

| 板厚 mm | 寸 法 mm | | | | | | | | | | | |
|----------|-------------|-----|--|-----------------|-------------|-----|--|-----------------|-------------|-----|--|-----------------|
| | 1250 x 3050 | | | | 1250 x 4000 | | | | 1525 x 3050 | | | |
| | 国内材 | 輸入材 | | 1枚の質量 (kg/枚) | 国内材 | 輸入材 | | 1枚の質量 (kg/枚) | 国内材 | 輸入材 | | 1枚の質量 (kg/枚) |
| 1.5 | ○ | | | 15.5 | | | | | ○ | | | 18.9 |
| 2.0 | ○ | ▲ | | 20.7 | | ▲ | | 27.10 | ○ | ▲ | | 25.2 |
| 3.0 | | | | | | | | | ○ | | | 37.8 |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |

表記の質量はテーブル計算です。実際の商品とは異なる場合があります。

アルミ定尺板4(A5052P・アルハイス・アルジェイド)

A5052P

○ H32又は34

△ アルハイス

□ アルジェイド

| 板厚 mm | 寸 法 mm | | | | | | | |
|-------|-------------|-------|--------|-----------------|-------------|-------|--------|-----------------|
| | 1000 × 2000 | | | | 1250 × 2500 | | | |
| | H32/H34 | アルハイス | アルジェイド | 1枚の質量 (kg/枚) | H32/H34 | アルハイス | アルジェイド | 1枚の質量 (kg/枚) |
| 0.5 | ○ | | | 2.68 | | | | |
| 0.8 | ○ | | | 4.29 | | | | |
| 1.0 | ○ | | | 5.36 | ○ | | | 8.38 |
| 1.2 | ○ | | | 6.43 | ○ | | | 10.06 |
| 1.5 | ○ | | | 8.04 | ○ | | | 12.56 |
| 2.0 | ○ | | | 10.72 | ○ | | | 16.75 |
| 2.5 | ○ | | | 13.40 | ○ | | | 20.94 |
| 3.0 | ○ | | | 16.08 | ○ | | | 25.14 |
| 4.0 | | △ | □ | 21.50 | | △ | □ | 33.50 |
| 5.0 | | △ | □ | 27.00 | | △ | □ | 42.00 |
| 6.0 | | △ | □ | 32.20 | | △ | □ | 50.30 |
| 8.0 | | △ | □ | 43.00 | | △ | □ | 67.40 |
| 10.0 | | △ | □ | 54.00 | | △ | □ | 84.10 |
| 12.0 | | △ | □ | 64.80 | | △ | □ | 100.90 |
| 15.0 | | △ | □ | 81.00 | | △ | □ | 126.20 |
| 16.0 | | △ | □ | 86.00 | | △ | □ | 134.70 |
| 18.0 | | △ | □ | 97.00 | | △ | □ | 151.50 |
| 20.0 | | △ | □ | 108.00 | | △ | □ | 168.20 |
| 22.0 | | △ | □ | 119.00 | | △ | □ | 185.00 |
| 25.0 | | △ | □ | 135.00 | | △ | □ | 210.20 |
| 30.0 | | △ | □ | 162.00 | | △ | □ | 252.40 |
| 35.0 | | △ | □ | 189.00 | | | | |
| 40.0 | | △ | □ | 216.00 | | | | |
| 45.0 | | | □ | 243.00 | | | | |
| 50.0 | | | □ | 269.50 | | | | |
| 55.0 | | | □ | 297.00 | | | | |
| 60.0 | | | □ | 324.00 | | | | |

表記の質量はテーブル計算です。実際の商品とは異なる場合があります。

アルミ定尺板5(A2017P)

A2017P

| 板厚 mm | 寸 法 mm | |
|-------|-------------|-------------|
| | 1000 x 2000 | |
| | 生地 | 1枚の質量(kg/枚) |
| 0.8 | | 4.50 |
| 1.0 | ○ | 5.60 |
| 1.5 | ○ | 8.40 |
| 2.0 | ○ | 11.2 |
| 3.0 | ○ | 16.8 |
| 4.0 | ○ | 22.4 |
| 5.0 | | 28.0 |
| 6.0 | | 33.5 |
| 8.0 | | 44.9 |
| 10.0 | ○ | 56.0 |
| 12.0 | ○ | 67.2 |
| 15.0 | ○ | 84.0 |
| 20.0 | ○ | 112.0 |
| 25.0 | ○ | 140.0 |
| 30.0 | ○ | 168.0 |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

表記の質量はテーブル計算です。実際の商品とは異なる場合があります。

アルミ定尺板6(縞板)

縞板(輸入品) A5052P

| 板厚 mm | 寸 法 mm | | | | | |
|-------|-------------|-------------|-------------|-------------|-------------|-------------|
| | 1000 x 2000 | | 1250 x 2500 | | 1525 x 3050 | |
| | 縞板(5本線) | 1枚の質量(kg/枚) | 縞板(5本線) | 1枚の質量(kg/枚) | 縞板(5本線) | 1枚の質量(kg/枚) |
| 2.0 | ○ | 12.5 | ○ | 19.7 | | |
| 2.5 | ○ | 15.2 | ○ | 23.9 | | |
| 3.0 | ○ | 18.0 | ○ | 28.1 | ○ | 40.0 |
| 3.5 | ○ | 21.7 | ○ | 32.3 | | 48.8 |
| 4.5 | ○ | 27.0 | ○ | 40.8 | | 60.0 |
| 6.0 | ○ | 36.0 | ○ | 53.4 | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

表記の質量はテーブル計算です。実際の商品とは異なる場合があります。

アルミコイル

A1050

| 寸 法 mm | 1本の質量(kg/本) | M当りの質量(kg/m) |
|-------------------|-------------|--------------|
| 0.3 x 1000 x 小コイル | ○ 50.0 | 0.813 |
| 0.4 x 1000 x 小コイル | ○ 50.0 | 1.084 |
| 0.5 x 1000 x 小コイル | ○ 50.0 | 1.355 |
| 0.6 x 1000 x 小コイル | ○ 50.0 | 1.626 |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |


表記の質量はテーブル質量です。実際の商品とは異なる場合があります

カラーアルミコイル

| 板厚 mm | 0.40 | 0.50 | 0.60 | 0.80 |
|--------------|------|------|------|------|
| 幅 mm | 914 | 914 | 914 | 914 |
| m当りの質量(kg/m) | 1.00 | 1.25 | 1.50 | 2.00 |
| シルバー | ○ | ○ | ○ | ○ |
| ブロンズ | ○ | | ○ | |
| ホワイト | | | ○ | |
| クリーム | | | ○ | |
| Dブラック改 | | | ○ | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

表記の質量はテーブル質量です。実際の商品とは異なる場合があります

アルミ丸管(引抜丸管)A1070TD・A5052TD



定尺 4,000mm


○ A1070TD

☆ A5052TD

| 外径 D mm | 肉 厚 t mm | | | | | | | | |
|---------|----------|-----|-----|-----|-----|-----|-----|-----|----------|
| | 0.8 | 1.0 | 1.4 | 1.5 | 2.0 | 3.0 | 4.0 | 5.0 | その他 |
| 6 | | ○ | | | | | | | |
| 8 | ○ | ○ | ☆ | | | | | | |
| 10 | | ○ | ☆ | ○ | | | | | |
| 12 | | ○ ☆ | | | ○ | | | | |
| 12.7 | | ○ | | | | | | | |
| 14 | | ○ | | | ○ | | | | |
| 15 | | ○ | ☆ | | | | | | |
| 16 | | ○ | | ○ | ○ ☆ | ☆ | | | |
| 17 | | ○ | | | | | | | |
| 18 | | ○ | | ○ | | | | | |
| 19 | | ○ ☆ | | ○ | ○ ☆ | ○ | | | |
| 20 | | ○ | ☆ | ○ | ○ ☆ | ☆ | | | |
| 22 | | ○ | | ○ | ○ ☆ | ☆ | | | |
| 25 | | ○ | | ○ | ○ ☆ | ○ ☆ | | | ☆ t=1.6 |
| 28 | | | | | ○ ☆ | ☆ | | | ☆ t=1.6 |
| 30 | | ○ | ☆ | | ○ ☆ | ○ ☆ | | | |
| 32 | | | | | ○ ☆ | ○ ☆ | | | |
| 35 | | | | | ○ ☆ | ○ ☆ | | | |
| 38 | | | | | ○ ☆ | ○ ☆ | ☆ | ☆ | ☆ t=3.75 |
| 40 | | ○ | | | ○ ☆ | ○ ☆ | ○ ☆ | ☆ | |
| 42 | | | | | ○ | | | | |
| 43 | | | | ○ | | | | | |
| 45 | | | | | ○ ☆ | ○ ☆ | | ○ ☆ | |
| 50 | | | | ○ | ○ ☆ | ○ ☆ | ○ ☆ | ○ ☆ | |
| 55 | | | | | | | | ☆ | ☆ t=8.0 |
| 60 | | | | | ☆ | ○ ☆ | ○ ☆ | ○ ☆ | |
| 65 | | | | | | ○ ☆ | | ○ ☆ | |
| 70 | | | | | | ○ ☆ | | ○ ☆ | |
| 75 | | | | | | ○ ☆ | | ○ ☆ | |
| 80 | | | | | | ○ ☆ | ☆ | ○ ☆ | |
| 85 | | | | | | | | ○ | |
| 90 | | | | | | ○ | ☆ | ○ ☆ | |
| 100 | | | | | | ○ ☆ | ○ | ○ ☆ | |
| 110 | | | | | | ○ | | ○ ☆ | |
| 120 | | | | | | ○ | ☆ | ○ ☆ | |
| 130 | | | | | | ○ ☆ | | ○ ☆ | |
| 140 | | | | | | | | ☆ | |
| 150 | | | | | | ○ | | ○ ☆ | |
| 165 | | | | | | | | ○ | |

アルミ四角管(63角パイプ)

A6063-T5




| 寸 法 mm | | | 1本の質量 (kg/本) | 寸 法 mm | | | 1本の質量 (kg/本) |
|--------|------|-------|-----------------|--------|------|------|-----------------|
| 辺 A | 肉厚 t | 定尺長さ | | 辺 A | 肉厚 t | 定尺長さ | |
| 9 | 1.2 | 5,000 | 0.510 | | | | |
| 10 | 1.0 | 〃 | 0.485 | | | | |
| 12 | 1.2 | 〃 | 0.705 | | | | |
| 15 | 1.2 | 〃 | 0.900 | | | | |
| | 1.5 | 〃 | 1.095 | | | | |
| 19 | 1.5 | 〃 | 1.420 | | | | |
| 20 | 1.5 | 〃 | 1.500 | | | | |
| | 2.0 | 〃 | 1.945 | | | | |
| | 2.5 | 〃 | 2.365 | | | | |
| 25 | 1.5 | 〃 | 1.905 | | | | |
| | 2.0 | 〃 | 2.495 | | | | |
| | 2.5 | 〃 | 3.040 | | | | |
| 30 | 1.5 | 〃 | 2.310 | | | | |
| | 2.0 | 〃 | 3.025 | | | | |
| | 3.0 | 〃 | 4.375 | | | | |
| 40 | 2.0 | 〃 | 4.105 | | | | |
| | 2.5 | 〃 | 5.065 | | | | |
| | 3.0 | 〃 | 5.995 | | | | |
| 50 | 2.0 | 〃 | 5.185 | | | | |
| | 2.5 | 〃 | 6.415 | | | | |
| | 3.0 | 〃 | 7.615 | | | | |
| 60 | 2.0 | 〃 | 6.265 | | | | |
| | 2.5 | 〃 | 7.760 | | | | |
| 70 | 2.0 | 〃 | 7.345 | | | | |
| 80 | 2.0 | 〃 | 8.425 | | | | |
| | 2.5 | 〃 | 10.465 | | | | |
| 100 | 2.5 | 〃 | 13.165 | | | | |
| | 3.0 | 〃 | 15.715 | | | | |
| | | | | | | | |

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

アルミ平角管(63平角パイプ)


A6063-T5



| 寸 法 mm | | | | 1本の 質量 (kg/本) | 寸 法 mm | | | | 1本の 質量 (kg/本) |
|--------|-----|------|-------|---------------------|--------|-----|------|-------|---------------------|
| 辺 A | 辺 B | 肉厚 t | 定尺長さ | | 辺 A | 辺 B | 肉厚 t | 定尺長さ | |
| 20 | 10 | 1.2 | 5,000 | 0.895 | 70 | 30 | 2.0 | 5,000 | 5.185 |
| | 15 | 1.5 | " | 1.295 | | 30 | 3.0 | " | 7.615 |
| 25 | 15 | 1.5 | " | 1.505 | | 50 | 2.0 | " | 6.265 |
| | 15 | 2.0 | " | 1.945 | 80 | 40 | 2.0 | " | 6.265 |
| 30 | 15 | 1.5 | " | 1.705 | | 40 | 2.5 | " | 7.765 |
| | 15 | 2.0 | " | 2.225 | | 40 | 3.0 | " | 9.235 |
| | 20 | 1.5 | " | 1.905 | 100 | 30 | 2.5 | " | 8.440 |
| | 20 | 2.0 | " | 2.485 | | 50 | 2.0 | " | 7.885 |
| | 20 | 2.5 | " | 3.040 | | 50 | 2.5 | " | 9.790 |
| | 25 | 3.0 | " | 3.970 | | 50 | 3.0 | " | 11.665 |
| 40 | 20 | 1.5 | " | 2.310 | | 80 | 2.7 | " | 12.760 |
| | 20 | 2.0 | " | 3.035 | 110 | 40 | 2.0 | " | 7.915 |
| | 20 | 2.5 | " | 3.715 | 120 | 60 | 2.8 | " | 13.190 |
| | 20 | 3.0 | " | 4.375 | 150 | 50 | 2.5 | " | 13.165 |
| | 25 | 3.0 | " | 4.780 | | 50 | 3.0 | " | 15.715 |
| | 30 | 1.5 | " | 2.780 | | | | | |
| | 30 | 2.0 | " | 3.565 | | | | | |
| | 30 | 3.0 | " | 5.185 | | | | | |
| 50 | 25 | 1.5 | " | 2.925 | | | | | |
| | 25 | 2.0 | " | 3.835 | | | | | |
| | 30 | 2.0 | " | 4.105 | | | | | |
| 60 | 25 | 2.0 | " | 4.375 | | | | | |
| | 30 | 1.5 | " | 3.535 | | | | | |
| | 30 | 2.0 | " | 4.650 | | | | | |
| | 30 | 2.5 | " | 5.740 | | | | | |
| | 40 | 2.0 | " | 5.185 | | | | | |
| | 40 | 2.5 | " | 6.415 | | | | | |
| | 40 | 3.0 | " | 7.615 | | | | | |
| | 40 | 4.0 | " | 9.935 | | | | | |

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

アルミ丸棒(1)




▲ L=2000

○ L=4000

| 直径 D mm | 材 質 | | | | | | | A1070 1mの質量 (Kg/m) |
|------------|---------------|-------------------|----------------|----------------|-------------------|-----------------------------|-------------------|--------------------------|
| | A1070 (1S) | A2017-T4 (17S) | A5052 (52S) | A5056 (56S) | A6061-T6 (61S) | C6PT8 (A2011) (11S相当) | A6063-T5 (63S) | |
| 3 | ▲ | | ▲ | | | | | 0.019 |
| 4 | ▲ | | ▲ | | | | | 0.034 |
| 5 | ▲ | ▲ | ▲ | | | ▲ | | 0.053 |
| 6 | ▲ | ▲ | ▲ | | | ▲ | | 0.076 |
| 7 | ▲ | ▲ | ▲ | | | ▲ | | 0.104 |
| 8 | ▲ | ▲ | ▲ | ○ | | ▲ | ○ | 0.136 |
| 9 | ▲ | ▲ | ▲ | | | ▲ | ○ | 0.175 |
| 10 | ○ | ○ | ○ | ○ | ○ | ▲ | ○ | 0.212 |
| 11 | ○ | ○ | ○ | | | ▲ | | 0.257 |
| 12 | ○ | ○ | ○ | ○ | | ▲ | ○ | 0.307 |
| 13 | ○ | ○ | ○ | ○ | | | ○ | 0.359 |
| 14 | ○ | ○ | ○ | ○ | | ▲ | | 0.417 |
| 15 | ○ | ○ | ○ | ○ | | ▲ | ○ | 0.478 |
| 16 | ○ | ○ | ○ | ○ | ○ | ▲ | ○ | 0.549 |
| 17 | ○ | ○ | ○ | ○ | | | | 0.615 |
| 18 | ○ | ○ | ○ | ○ | | | | 0.690 |
| 19 | ○ | ○ | ○ | ○ | ○ | | | 0.768 |
| 20 | ○ | ○ | ○ | ○ | ○ | | ○ | 0.852 |
| 21 | | ○ | | | | | | 0.939 |
| 22 | ○ | ○ | ○ | ○ | | | ○ | 1.030 |
| 23 | | ○ | | | | | | 1.126 |
| 24 | | ○ | | | | | | 1.226 |
| 25 | ○ | ○ | ○ | ○ | ○ | | ○ | 1.330 |
| 26 | ○ | ○ | ○ | ○ | | | | 1.438 |
| 28 | ○ | ○ | ○ | ○ | | | | 1.669 |
| 30 | ○ | ○ | ○ | ○ | ○ | | ○ | 1.916 |
| 32 | ○ | ○ | ○ | ○ | ○ | | ○ | 2.180 |
| 33 | | ○ | | | | | | 2.371 |
| 34 | | ○ | | | | | | 2.461 |
| 35 | ○ | ○ | ○ | ○ | ○ | | | 2.608 |
| 36 | ○ | ○ | ○ | ○ | | | | 2.800 |
| 38 | ○ | ○ | ○ | ○ | | | | 3.104 |
| 40 | ○ | ○ | ○ | ○ | ○ | | ○ | 3.406 |
| 42 | ○ | ○ | ○ | ○ | ○ | | | 3.754 |
| 45 | ○ | ○ | ○ | ○ | ○ | | ○ | 4.310 |
| 46 | | ○ | | | | | | 4.501 |
| 48 | | ○ | ○ | ○ | | | | 4.901 |
| 50 | ○ | ○ | ○ | ○ | ○ | | ○ | 5.321 |

表記の質量はテーブル質量です。実際の商品とは異なる場合があります

アルミ丸棒(2)



▲ L=2000


○ L=4000

| 直径 D mm | 材 質 | | | | | | | A1070 1mの質量 (Kg/m) |
|------------|---------------|-------------------|----------------|----------------|-------------------|-----------------------------|-------------------|--------------------------|
| | A1070 (1S) | A2017-T4 (17S) | A5052 (52S) | A5056 (56S) | A6061-T6 (61S) | C6PT8 (A2011) (11S相当) | A6063-T5 (63S) | |
| 52 | | ○ | | | | | | 5.753 |
| 55 | ○ | ○ | ○ | ○ | ○ | | | 6.438 |
| 60 | ○ | ○ | ○ | ○ | ○ | | ○ | 7.719 |
| 65 | ○ | ○ | ○ | ○ | ○ | | | 9.056 |
| 70 | ▲ | ○ | ▲ | ▲ | ▲ | | | 10.506 |
| 75 | ▲ | ○ | ▲ | ▲ | ▲ | | | 12.061 |
| 80 | ▲ | ○ | ▲ | ▲ | ▲ | | | 13.722 |
| 85 | ▲ | ○ | ▲ | ▲ | ▲ | | | 15.377 |
| 90 | ▲ | ○ | ▲ | ▲ | ▲ | | | 17.241 |
| 95 | ▲ | ○ | ▲ | ▲ | ▲ | | | 19.205 |
| 100 | ▲ | ○ | ▲ | ▲ | ▲ | | | 21.284 |
| 105 | | ▲ | | | | | | 23.550 |
| 110 | ▲ | ▲ | ▲ | ▲ | ▲ | | | 25.754 |
| 115 | | ▲ | | | | | | 28.013 |
| 120 | ▲ | ▲ | ▲ | ▲ | ▲ | | | 30.649 |
| 130 | ▲ | ▲ | ▲ | ▲ | ▲ | | | 35.963 |
| 140 | ▲ | ▲ | ▲ | ▲ | ▲ | | | 41.650 |
| 150 | ▲ | ▲ | ▲ | ▲ | ▲ | | | 47.800 |
| 160 | ▲ | ▲ | ▲ | ▲ | ▲ | | | 54.900 |
| 170 | | ▲ | ▲ | ▲ | ▲ | | | 61.480 |
| 180 | | ▲ | ▲ | ▲ | ▲ | | | 69.000 |
| 190 | | ▲ | ▲ | ▲ | ▲ | | | 76.800 |
| 200 | | ▲ | ▲ | ▲ | ▲ | | | 85.200 |
| 210 | | ▲ | | ▲ | ▲ | | | 93.820 |
| 220 | | ▲ | | ▲ | ▲ | | | 103.000 |
| 230 | | ▲ | | ▲ | ▲ | | | 112.600 |
| 240 | | ▲ | | ▲ | ▲ | | | 122.600 |
| 250 | | ▲ | | ▲ | ▲ | | | 133.000 |
| 260 | | ▲ | | ▲ | ▲ | | | 143.800 |
| 270 | | ▲ | | ▲ | ▲ | | | 156.700 |
| 280 | | ▲ | | ▲ | ▲ | | | 166.900 |
| 290 | | ▲ | | ▲ | | | | 178.700 |
| 300 | | ▲ | | ▲ | ▲ | | | 191.600 |
| 310 | | ▲ | | ▲ | | | | 204.500 |
| 320 | | ▲ | | ▲ | | | | 217.900 |
| 330 | | ▲ | | ▲ | | | | 231.700 |
| 340 | | ▲ | | ▲ | | | | 246.000 |
| 350 | | ▲ | | ▲ | | | | 260.700 |

表記の質量はテーブル質量です。実際の商品とは異なる場合があります

アルミ四角棒 (63角棒)

A6063-T5




| 寸 法 mm | | 1本の質量 (kg/本) | 寸 法 mm | | 1本の質量 (kg/本) |
|--------|--------|-----------------|--------|------|-----------------|
| 辺 A | 定尺長さ | | 辺 A | 定尺長さ | |
| 5 | 4,000 | 0.272 | | | |
| 6 | " | 0.388 | | | |
| 7 | " | 0.524 | | | |
| 8 | " | 0.692 | | | |
| 9 | " | 0.876 | | | |
| 10 | " | 1.080 | | | |
| 12 | " | 1.556 | | | |
| 13 | " | 1.824 | | | |
| 14 | " | 2.116 | | | |
| 15 | " | 2.432 | | | |
| 16 | " | 2.764 | | | |
| 18 | " | 3.512 | | | |
| 19 | " | 3.900 | | | |
| 20 | " | 4.336 | | | |
| 22 | " | 5.220 | | | |
| 25 | " | 6.776 | | | |
| 30 | " | 9.720 | | | |
| 32 | " | 11.060 | | | |
| 35 | " | 13.232 | | | |
| 38 | " | 15.596 | | | |
| 40 | " | 17.344 | | | |
| 45 | " | 21.872 | | | |
| 50 | " | 27.000 | | | |
| 55 | " | 32.672 | | | |
| 60 | L=3000 | 29.160 | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

アルミ平角棒 (63平角棒) 1

A6063-T5




| 寸 法 mm | | | 1本の 質量 (kg/本) | 寸 法 mm | | | 1本の 質量 (kg/本) | 寸 法 mm | | | 1本の 質量 (kg/本) | |
|--------|-----|-------|---------------------|--------|-------|-------|---------------------|--------|-------|-------|---------------------|-------|
| 厚さA | 幅 B | 定尺長さ | | 厚さA | 幅 B | 定尺長さ | | 厚さA | 幅 B | 定尺長さ | | |
| 2 | 10 | 4,000 | 0.216 | 4 | 60 | 4,000 | 2.592 | 8 | 15 | 4,000 | 1.296 | |
| | 12 | " | 0.260 | | 70 | " | 3.024 | | 20 | " | 1.728 | |
| | 15 | " | 0.324 | | 5 | 10 | " | | 0.540 | 25 | " | 2.160 |
| | 20 | " | 0.432 | 15 | | " | 0.812 | | 30 | " | 2.592 | |
| | 25 | " | 0.540 | 20 | | " | 1.084 | | 32 | " | 2.772 | |
| | 30 | " | 0.648 | 25 | | " | 1.352 | | 35 | " | 3.024 | |
| | 35 | " | 0.756 | 30 | | " | 1.620 | | 40 | " | 3.456 | |
| | 40 | " | 0.864 | 35 | | " | 1.892 | | 50 | " | 4.320 | |
| | 50 | " | 1.080 | 40 | " | 2.160 | 60 | | " | 5.184 | | |
| 3 | 10 | " | 0.324 | 50 | " | 2.700 | 9 | 75 | " | 6.480 | | |
| | 12 | " | 0.388 | 60 | " | 3.240 | | 100 | " | 8.640 | | |
| | 15 | " | 0.488 | 70 | " | 3.780 | | 10 | 20 | " | 1.944 | |
| | 16 | " | 0.520 | 75 | " | 4.052 | | | 30 | " | 2.916 | |
| | 20 | " | 0.648 | 100 | " | 5.400 | | | 40 | " | 3.888 | |
| | 25 | " | 0.812 | 6 | 10 | " | | | 0.648 | 50 | " | 4.860 |
| | 30 | " | 0.972 | | 12 | " | | | 0.776 | 60 | " | 5.832 |
| | 35 | " | 1.136 | | 15 | " | | | 0.976 | 75 | " | 7.292 |
| | 40 | " | 1.296 | | 20 | " | | 1.296 | 100 | " | 9.720 | |
| | 50 | " | 1.620 | | 25 | " | | 1.620 | 15 | " | 1.620 | |
| | 60 | " | 1.944 | 30 | " | 1.944 | | 20 | " | 2.168 | | |
| 70 | " | 2.268 | 32 | " | 2.076 | 25 | " | 2.700 | | | | |
| 4 | 10 | " | 0.432 | 35 | " | 2.268 | 10 | 30 | " | 3.240 | | |
| | 12 | " | 0.520 | 40 | " | 2.592 | | 35 | " | 3.780 | | |
| | 15 | " | 0.648 | 45 | " | 2.916 | | 40 | " | 4.320 | | |
| | 20 | " | 0.868 | 50 | " | 3.240 | | 45 | " | 4.860 | | |
| | 25 | " | 1.080 | 60 | " | 3.888 | | 50 | " | 5.420 | | |
| | 30 | " | 1.300 | 65 | " | 4.212 | | 60 | " | 6.480 | | |
| | 40 | " | 1.728 | 75 | " | 4.860 | | 70 | " | 7.560 | | |
| | 50 | " | 2.160 | 100 | " | 6.480 | | 75 | " | 8.132 | | |

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

アルミ平角棒 (63平角棒) 2

A6063-T5




| 寸 法 mm | | | 1本の 質量 (kg/本) | 寸 法 mm | | | 1本の 質量 (kg/本) | 寸 法 mm | | | 1本の 質量 (kg/本) | |
|--------|-----|--------|---------------------|--------|-------|--------|---------------------|--------|-----|------|---------------------|--|
| 厚さA | 幅 B | 定尺長さ | | 厚さA | 幅 B | 定尺長さ | | 厚さA | 幅 B | 定尺長さ | | |
| 10 | 80 | 4,000 | 8.640 | 20 | 65 | 4,000 | 14.040 | | | | | |
| | 100 | " | 10.840 | | 70 | " | 15.120 | | | | | |
| | 120 | " | 12.960 | | 80 | " | 17.280 | | | | | |
| | 125 | " | 13.500 | | 100 | " | 21.680 | | | | | |
| | 150 | " | 16.200 | | 150 | " | 32.400 | | | | | |
| 12 | 20 | " | 2.592 | 25 | 30 | " | 8,100 | | | | | |
| | 25 | " | 3.240 | | 35 | " | 9.452 | | | | | |
| | 30 | " | 3.888 | | 40 | " | 10.800 | | | | | |
| | 40 | " | 5.180 | | 50 | " | 13.500 | | | | | |
| | 50 | " | 6.504 | | 60 | " | 16.200 | | | | | |
| | 60 | " | 7.776 | | 80 | " | 21.600 | | | | | |
| | 75 | " | 9.720 | | 100 | " | 27.000 | | | | | |
| | 100 | " | 12.960 | | 30 | 40 | " | 12.960 | | | | |
| 120 | " | 15.552 | 50 | " | | 16.200 | | | | | | |
| 15 | 20 | " | 3.252 | 60 | | " | 19.440 | | | | | |
| | 25 | " | 4.052 | 65 | | " | 21.060 | | | | | |
| | 30 | " | 4.860 | 75 | | " | 24.300 | | | | | |
| | 40 | " | 6.480 | 100 | | " | 32.400 | | | | | |
| | 50 | " | 8.100 | 35 | | 40 | " | 15.120 | | | | |
| | 60 | " | 9.720 | | | 50 | " | 18.900 | | | | |
| | 75 | " | 12.148 | | 60 | " | 22.680 | | | | | |
| | 100 | " | 16.200 | | 85 | " | 32.132 | | | | | |
| 20 | 150 | " | 24.300 | 40 | 100 | 2,500 | 23.625 | | | | | |
| | 25 | " | 5.400 | | 50 | 4,000 | 21.600 | | | | | |
| | 30 | " | 6.504 | | 60 | " | 25.920 | | | | | |
| | 35 | " | 7.560 | | 75 | " | 32.400 | | | | | |
| | 40 | " | 8.672 | 100 | 2,500 | 27.000 | | | | | | |
| | 50 | " | 10.800 | | | | | | | | | |
| | 60 | " | 12.960 | | | | | | | | | |

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

アルミチャンネル(63チャンネル)


A6063-T5

Rナシチャンネル



| 寸 法 mm | | | | 1本の 質量 (kg/本) | 寸 法 mm | | | | 1本の 質量 (kg/本) |
|--------|----|------|-------|---------------------|--------|----|------|-------|---------------------|
| A | B | 肉厚 t | 定尺長さ | | A | B | 肉厚 t | 定尺長さ | |
| 10 | 10 | 1.6 | 5,000 | 0.580 | 50 | 25 | 3.0 | 5,000 | 3.805 |
| 15 | 15 | 1.5 | " | 0.860 | 60 | 30 | 3.0 | " | 4.615 |
| | 15 | 2.0 | " | 1.105 | 75 | 40 | 3.2 | " | 6.425 |
| 18 | 10 | 2.0 | " | 0.920 | | 50 | 5.0 | " | 11.140 |
| 20 | 20 | 2.0 | " | 1.515 | 80 | 40 | 4.0 | " | 8.210 |
| 25 | 15 | 2.0 | " | 1.375 | 100 | 50 | 5.0 | " | 12.825 |
| | 25 | 2.0 | " | 1.915 | 125 | 65 | 6.0 | " | 19.685 |
| 30 | 15 | 2.0 | " | 1.510 | | | | | |
| | 25 | 3.0 | " | 2.995 | | | | | |
| | 30 | 2.4 | " | 2.765 | | | | | |
| 35 | 20 | 2.4 | " | 2.275 | | | | | |
| 40 | 20 | 2.0 | " | 2.050 | | | | | |
| | 20 | 3.0 | " | 2.995 | | | | | |
| 50 | 25 | 2.5 | " | 3.205 | | | | | |

R付きチャンネル




| 寸 法 mm | | | | 1本の 質量 (kg/本) | R1 | R2 |
|--------|----|------|-------|---------------------|-----|-----|
| A | B | 肉厚 t | 定尺長さ | | | |
| 75 | 40 | 6.0 | 5,000 | 11.585 | 5.0 | 5.0 |
| 100 | 50 | 5.0 | " | 12.745 | 3.0 | 5.0 |
| 125 | 65 | 6.0 | " | 19.845 | 6.0 | 3.0 |
| 150 | 75 | 8.0 | " | 30.76 | 8.0 | 7.0 |

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

アルミ等辺アングル Rナシ (63アングル)

A6063-T5




| 寸 法 mm | | | 1本の質量 (kg/本) | 寸 法 mm | | | 1本の質量 (kg/本) |
|--------|------|-------|-----------------|--------|------|-------|-----------------|
| 辺 A | 厚さ t | 定尺長さ | | 辺 A | 厚さ t | 定尺長さ | |
| 9 | 1.0 | 4,000 | 0.184 | 40 | 2.0 | 4,000 | 1.684 |
| 10 | 1.0 | " | 0.204 | | 3.0 | " | 2.496 |
| | 1.2 | " | 0.244 | | 4.0 | " | 3.284 |
| 12 | 1.2 | " | 0.296 | | 5.0 | " | 4.052 |
| 15 | 1.0 | " | 0.312 | | 6.0 | " | 4.796 |
| | 1.5 | " | 0.464 | 50 | 1.5 | " | 1.596 |
| | 2.0 | " | 0.604 | | 3.0 | " | 3.144 |
| | 3.0 | " | 0.872 | | 4.0 | " | 4.148 |
| 19 | 1.0 | " | 0.400 | | 5.0 | " | 5.132 |
| | 1.5 | " | 0.592 | 6.0 | " | 6.092 | |
| 20 | 1.5 | " | 0.624 | 60 | 5.0 | " | 6.212 |
| | 2.0 | " | 0.820 | | 6.0 | " | 7.388 |
| | 3.0 | " | 1.200 | 65 | 6.0 | " | 8.036 |
| 25 | 1.0 | " | 0.528 | | 8.0 | " | 10.540 |
| | 1.2 | " | 0.636 | 70 | 4.0 | " | 5.876 |
| | 1.5 | " | 0.784 | 75 | 6.0 | " | 9.332 |
| | 2.0 | " | 1.036 | | 9.0 | " | 13.704 |
| | 3.0 | " | 1.524 | 80 | 8.0 | " | 13.132 |
| | 4.0 | " | 1.988 | 100 | 10.0 | " | 20.520 |
| | 5.0 | " | 2.432 | | | | |
| 30 | 1.0 | " | 0.636 | | | | |
| | 1.2 | " | 0.764 | | | | |
| | 1.5 | " | 0.948 | | | | |
| | 2.0 | " | 1.256 | | | | |
| | 3.0 | " | 1.848 | | | | |
| | 4.0 | " | 2.420 | | | | |
| 35 | 5.0 | " | 2.980 | | | | |
| | 3.0 | " | 2.172 | | | | |
| | 4.0 | " | 2.852 | | | | |

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

アルミ不等辺アングル Rナシ (63アングル)

A6063-T5




| 寸 法 mm | | | | 1本の質量 (kg/本) |
|--------|-----|------|-------|-----------------|
| 辺 A | 辺 B | 厚さ t | 定尺長さ | |
| 15 | 10 | 1.5 | 4,000 | 0.380 |
| | 10 | 2.0 | 〃 | 0.496 |
| 20 | 10 | 1.5 | 〃 | 0.464 |
| | 15 | 1.5 | 〃 | 0.540 |
| | 15 | 2.0 | 〃 | 0.712 |
| 25 | 15 | 1.5 | 〃 | 0.624 |
| | 15 | 2.0 | 〃 | 0.820 |
| | 15 | 3.0 | 〃 | 1.200 |
| | 20 | 2.0 | 〃 | 0.928 |
| 30 | 10 | 1.5 | 〃 | 0.624 |
| | 15 | 1.5 | 〃 | 0.704 |
| | 15 | 2.0 | 〃 | 0.928 |
| | 15 | 3.0 | 〃 | 1.360 |
| | 20 | 2.0 | 〃 | 1.036 |
| | 20 | 3.0 | 〃 | 1.524 |
| 40 | 10 | 1.5 | 〃 | 0.788 |
| | 20 | 2.0 | 〃 | 1.252 |
| | 20 | 3.0 | 〃 | 1.848 |
| | 30 | 3.0 | 〃 | 2.172 |
| 50 | 25 | 3.0 | 〃 | 2.332 |
| | 35 | 4.0 | 〃 | 3.500 |
| 60 | 40 | 5.0 | 〃 | 5.132 |
| | 50 | 5.0 | 〃 | 5.672 |
| 75 | 50 | 5.0 | 〃 | 6.480 |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

アルミアングル R付き (63アングル)


A6063-T5

等辺アングル



| 寸 法 mm | | | 1本の質量 (kg/本) | R1 | R2 |
|--------|------|-------|-----------------|-----|-----|
| 辺 A | 厚さ t | 定尺長さ | | | |
| 30 | 3.0 | 4,000 | 1.864 | 4.0 | 2.0 |
| 40 | 3.0 | 〃 | 2.524 | 4.5 | 2.0 |
| | 5.0 | 〃 | 4.056 | 4.5 | 3.0 |
| | 6.0 | 〃 | 4.836 | 6.0 | 3.0 |
| 50 | 5.0 | 〃 | 5.240 | 6.5 | 3.0 |
| | 6.0 | 〃 | 6.096 | 6.5 | 4.5 |
| 60 | 6.0 | 〃 | 7.484 | 8.5 | 4.0 |
| 65 | 6.0 | 〃 | 8.128 | 8.5 | 4.0 |
| | 8.0 | 〃 | 10.616 | 8.0 | 4.0 |
| 75 | 6.0 | 〃 | 9.456 | 6.0 | 3.0 |
| | 9.0 | 〃 | 13.804 | 8.5 | 4.0 |
| 80 | 8.0 | 〃 | 13.228 | 8.5 | 4.0 |
| 100 | 10.0 | 〃 | 20.640 | 8.5 | 4.0 |

不等辺アングル



| 寸 法 mm | | | | 1本の質量 (kg/本) | R1 | R2 |
|--------|-----|------|-------|-----------------|------|-----|
| 辺 A | 辺 B | 厚さ t | 定尺長さ | | | |
| 75 | 50 | 5.0 | 4,000 | 6.508 | 5.0 | 2.5 |
| 100 | 70 | 4.0 | 〃 | 7.256 | 5.0 | - |
| | 75 | 10.0 | 〃 | 17.936 | 10.0 | 5.0 |
| 125 | 75 | 12.0 | 〃 | 24.532 | 12.0 | 6.0 |
| | | | | | | |
| | | | | | | |

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。