


アルミ四角管(63角パイプ)

A6063-T5




寸 法 mm			1本の質量 (kg/本)	寸 法 mm			1本の質量 (kg/本)
辺 A	肉厚 t	定尺長さ		辺 A	肉厚 t	定尺長さ	
9	1.2	5,000	0.510				
10	1.0	〃	0.485				
12	1.2	〃	0.705				
15	1.2	〃	0.900				
	1.5	〃	1.095				
19	1.5	〃	1.420				
20	1.5	〃	1.500				
	2.0	〃	1.945				
	2.5	〃	2.365				
25	1.5	〃	1.905				
	2.0	〃	2.495				
	2.5	〃	3.040				
30	1.5	〃	2.310				
	2.0	〃	3.025				
	3.0	〃	4.375				
40	2.0	〃	4.105				
	2.5	〃	5.065				
	3.0	〃	5.995				
50	2.0	〃	5.185				
	2.5	〃	6.415				
	3.0	〃	7.615				
60	2.0	〃	6.265				
	2.5	〃	7.760				
70	2.0	〃	7.345				
80	2.0	〃	8.425				
	2.5	〃	10.465				
100	2.5	〃	13.165				
	3.0	〃	15.715				

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。

アルミ平角管(63平角パイプ)

A6063-T5



寸 法 mm				1本の 質量 (kg/本)	寸 法 mm				1本の 質量 (kg/本)
辺 A	辺 B	肉厚 t	定尺長さ		辺 A	辺 B	肉厚 t	定尺長さ	
20	10	1.2	5,000	0.895	70	30	2.0	5,000	5.185
	15	1.5	〃	1.295		30	3.0	〃	7.615
25	15	1.5	〃	1.505		50	2.0	〃	6.265
	15	2.0	〃	1.945	80	40	2.0	〃	6.265
30	15	1.5	〃	1.705		40	2.5	〃	7.765
	15	2.0	〃	2.225		40	3.0	〃	9.235
	20	1.5	〃	1.905	100	30	2.5	〃	8.440
	20	2.0	〃	2.485		50	2.0	〃	7.885
	20	2.5	〃	3.040		50	2.5	〃	9.790
	25	3.0	〃	3.970		50	3.0	〃	11.665
40	20	1.5	〃	2.310		80	2.7	〃	12.760
	20	2.0	〃	3.035	110	40	2.0	〃	7.915
	20	2.5	〃	3.715	120	60	2.8	〃	13.190
	20	3.0	〃	4.375	150	50	2.5	〃	13.165
	25	3.0	〃	4.780		50	3.0	〃	15.715
	30	1.5	〃	2.780					
	30	2.0	〃	3.565					
	30	3.0	〃	5.185					
50	25	1.5	〃	2.925					
	25	2.0	〃	3.835					
	30	2.0	〃	4.105					
60	25	2.0	〃	4.375					
	30	1.5	〃	3.535					
	30	2.0	〃	4.650					
	30	2.5	〃	5.740					
	40	2.0	〃	5.185					
	40	2.5	〃	6.415					
	40	3.0	〃	7.615					
	40	4.0	〃	9.935					

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。