


アルミチャンネル(63チャンネル)


A6063-T5

Rナシチャンネル



| 寸 法 mm | | | | 1本の 質量 (kg/本) | 寸 法 mm | | | | 1本の 質量 (kg/本) |
|--------|----|------|-------|---------------------|--------|----|------|-------|---------------------|
| A | B | 肉厚 t | 定尺長さ | | A | B | 肉厚 t | 定尺長さ | |
| 10 | 10 | 1.6 | 5,000 | 0.580 | 50 | 25 | 3.0 | 5,000 | 3.805 |
| 15 | 15 | 1.5 | " | 0.860 | 60 | 30 | 3.0 | " | 4.615 |
| | 15 | 2.0 | " | 1.105 | 75 | 40 | 3.2 | " | 6.425 |
| 18 | 10 | 2.0 | " | 0.920 | | 50 | 5.0 | " | 11.140 |
| 20 | 20 | 2.0 | " | 1.515 | 80 | 40 | 4.0 | " | 8.210 |
| 25 | 15 | 2.0 | " | 1.375 | 100 | 50 | 5.0 | " | 12.825 |
| | 25 | 2.0 | " | 1.915 | 125 | 65 | 6.0 | " | 19.685 |
| 30 | 15 | 2.0 | " | 1.510 | | | | | |
| | 25 | 3.0 | " | 2.995 | | | | | |
| | 30 | 2.4 | " | 2.765 | | | | | |
| 35 | 20 | 2.4 | " | 2.275 | | | | | |
| 40 | 20 | 2.0 | " | 2.050 | | | | | |
| | 20 | 3.0 | " | 2.995 | | | | | |
| 50 | 25 | 2.5 | " | 3.205 | | | | | |

R付きチャンネル



| 寸 法 mm | | | | 1本の 質量 (kg/本) | R1 | R2 |
|--------|----|------|-------|---------------------|-----|-----|
| A | B | 肉厚 t | 定尺長さ | | | |
| 75 | 40 | 6.0 | 5,000 | 11.585 | 5.0 | 5.0 |
| 100 | 50 | 5.0 | " | 12.745 | 3.0 | 5.0 |
| 125 | 65 | 6.0 | " | 19.845 | 6.0 | 3.0 |
| 150 | 75 | 8.0 | " | 30.76 | 8.0 | 7.0 |

表記の質量はテーブル質量です。実際の商品とは異なる場合があります。